

CNC Vertical Broaching Machine

CNC-3VT-1000

Better Cutting Performance

Rugged & Heavy Duty

Internal Broaching Operation

Highly Productive



Servo Controlled

CNC Vertical Broaching Machine (Pull Type) is most suited for Internal broaching operation. A vertical design saves costly floor space and eliminates sag of broach.

The machine is built of rigid fabricated bed, hard chrome plated columns. You can use simple broaching fixture and get good accuracies.

Both Servo motors are synchronized to achieve proper rapid & feed movement of cross head.

Technical Specifications	Units	Model 3 VT
Max. Pulling Force	kg.	3000
Broach Stroke	mm	500/1000/1200
Work Table	mm	325 x 680
Cutting Speed (Infinitely Variable)	m/min	1 to 5
Return Speed	m/min	12
Dia of bore in face plate	mm	Dia 65
lax. Broach Shank Dia.	mm	36
Power of Servo Motor - 2 Nos.	kW	1.5 each
Power of Coolant Motor	kW	0.25
Power of Auto Lubrication	kW	0.18
Total Power	kW	3.5
Coolant Tank Capacity	Ltrs	100
Machine Net Weight (Approx.)	kg.	1200

Standard Equipments:

- 1) Built in Coolant Equipment
- 2) Operating Service Tools
- 3) Splash Guards.
- 4) Operators Manual

Optional Accessories:

- 1) Broach pullers to suit broach shank
- 2) Broach guide bush for pull end to suit broach shank.
- 3) Broaching Fixture.

Due to continuous improvement of the product, SPM reserves all rights to change the above specifications without any prior notice.

Office Address:

Spm Tools, Block No. 7, Old Industrial Estate, Behind Central Bus Stand, Ichalkaranji, Dist. – Kolhapur, Maharashtra. INDIA - 416115,

Cell - +91 9850065886 / 9822019794

E-mail - marketing@spmtools.in

Web - www.spmtools.net



